



SUBSTITUTE SHEET (RULE 26)




SUBSTITUTE SHEET (RULE 26)



SUBSTITUTE SHEET (RULE 26)

4/21











Fig. 5
















Fig. 13

9/21





SUBSTITUTE SHEET (RULE 26)







Fig. 16



SUBSTITUTE SHEET (RULE 26)



SUBSTITUTE SHEET (RULE 26)



SUBSTITUTE SHEET (RULE 26)





Fig. 20







Fig. 22



Whenever a position capture is triggered, the trigger must be reset before another capture can occur.

The lug/pitch position capture trigger is automatically reset on the negative transition fo the lug/pitch sensor/signal. The product postion capture trigger is programmatically reset here.



CZLength:. Correction zone length (in inches) entered via the OPI.
Pitch: Distance between lugs/pitch marks (in inches) entered via the OPI.

-ugposn: Position (in encoder counts) of the lug/pitch mark.

ProdPosn: Position (in encoder counts) of the product.

JeltaPosn: Difference between LugPosn and ProdPosn. Distance (in inches) that the product leads/lags the lug/pitch mark.

ProdError: Product position error. Distance (in inches) that the product needs to be advanced/retarded so that it can match the position of the lug/pitch mark.

change the apparent position of the Lug/pitch mark sensor/signal instead of changing its PitchOffset: Manual lug/pitch mark adjustment factor (in inches) entered via the OPI. Can be used to actual physical position.

McorrDist: Master correction distance. Master axis encoder distance remaining to be used to make the ScorrDist: Slave correction distance. Correction zone motor distance moved during a correction index. correction index.

Variable Description





Fig. 25



SUBSTITUTE SHEET (RULE 26)